

Telehandler / Zoom Boom

Used Telehandler Alabama - Telehandlers are commonly known by a variety of names such as Cherry pickers, telescopic handlers, boom lifts and teleports. This industrial machine is commonly used in a variety of industries and in agriculture. Similar to a crane and a forklift as it has a boom allowing it to extend forwards and upwards. Numerous attachments can be placed at the end of the articulating boom to conduct a variety of different jobs. Popular attachments include a muck grab, bucket, winch or pallet forks. The main telehandler attachment is the pallet forks. Pallet forks enable the operator to move loads to and from a variety of locations that would otherwise be considered unreachable with a standard forklift. Telehandlers allow cargo pallets to be loaded and unloaded from a trailer and placed on high locations such as racking or rooftops. Typically, high locations would traditionally require a crane; however, telehandlers can facilitate these tasks easily and efficiently. Of course, it isn't always affordable or practical to use secondary equipment or a crane to complete certain tasks. A bucket grab or a bucket is the most common attachments for telehandlers within the agricultural sector. Moving items from unreachable locations that cannot be completed with a backhoe loader or wheeled loader give telehandlers a huge advantage. For instance, these industrial machines can directly access a hopper or trailer with high sides; applications that would otherwise rely on a conveyor, loading ramp or similar equipment. Having one item to complete a variety of jobs saves time, money and storage space. Telehandler machines can work in conjunction with a crane jib. Many attachments can be used such as power booms, grain and dirt buckets and rotators. Agricultural models can be outfitted with power take-off and 3-point linkage, making the telehandler and exceptionally useful. Interestingly enough, the machines' main advantage is also its' biggest limitation. When raising or extending with heavy loads, the boom functions similar to a lever. Despite significant counterweights in the rear, the telehandler can be subject to instability at times, decreasing the lifting capacity as the working radius or distance between the center of the load and the front of the wheels increases. If the machine works as a single boom loader instead of using twin arms while carrying a large load, there is a chance that weakness can occur even in the most carefully designed units. A machine with a 5K lb. capacity could safely lift 400 lbs. while fully extended using a retracted low boom angle. This unit with a 5000 lb. lift capability and retracted boom could support as much as ten thousand pounds after the boom is raised seventy degrees. There is a load chart on these machines to determine which tasks can be safely executed by taking the weight, angle and boom height into account. Newer telehandler models rely on computers and sensors to monitor the machine. When the telehandler limits have been surpassed, the operator is cut off and warned from supplying further control input. Front stabilizers that enhance the lifting capacity of the machine while stationary can make a huge difference. Another option is a stabilizing rotary joint between lower and upper frames, often referred to as a mobile crane that can additionally utilize a bucket. Compact telehandler models are available in a variety of different weights, reach, sizes and boom designs. If the machine weighs in at eleven thousand pounds or less, it can be part of the compact category. Compact models feature a two-stage boom design in comparison to the three or four boom design that is common with larger units. A low pivot boom ensures better operator visibility for transporting loads on compact units. Compact models are skinnier and have thinner dimensions. The compact units offer a reach capacity between thirteen to twenty feet and a lifting capacity ranging from five thousand to seven thousand pounds. There are many different applications this machine is suitable for working in. Telehandlers can function as a pick and place unit or a tool carrier. Compact units are ideal for cramped locations. Residential applications are common as contractors relish their useful nature with framing applications and where height restrictions come into play. These machines can facilitate internal building access. Compact telehandlers are used in many applications including nurseries, erecting steel, multi-story construction, masonry, strip malls, garages and similar jobs. Telehandlers are employed by agri-business and farming applications to complete many jobs. Telehandlers

come with crab steering or two or four-wheel drive options. This machine can traverse longer distances with two-wheel drive at higher speeds to facilitate easy travel between worksites. Four-wheel drive units can travel over harder terrain while offering a tighter turning radius. Crab steering increases overall maneuvering and enables the front and back wheels to move 45 degrees to the left or the right. There are a variety of cab interior options available for compact telehandlers. On the lower-end models, a rollover protective cage structure is in place for safety. Higher-end models are equipped with a fully enclosed cab, a heater, windshield wiper and defroster. Operators enjoy spacious accommodation for ultimate comfort. Additional features such as cup holders, air conditioning, tilt steering, suspension seats and satellite radio are all options. The numerous attachment options are facilitated with high-pressure and high-flow auxiliary hydraulics. The different attachments allow the machine to be capable of many options. All of these attachments enable the machine to conduct a variety of jobs. Compact machines conduct ground-engaging jobs. It is easy to enjoy the benefits of a mini excavator by adding a simple bucket attachment to the telehandler. Light and heavy-duty buckets can be used to move items, augers can plant trees or drill holes, rotating and side-shifting fork carriages facilitate pick-and-place, truss booms are in place for extending reach, sweeping brooms and crane hooks are other popular attachments. Skid steer attachments are being made for versatility and other compact telehandler designs.