

## Scissor Lift

Used Scissor Lift Alabama - Scissor lifts are industrial equipment that relies on steel linked arms to lift vertically. This equipment is utilized to create an "X" patterned support in order to accomplish vertical lifting. There is a rectangular platform that is attached to the top of the scissor lift. There are secure support railings along the platform edge for extra safety and to keep the operator safe. The scissor lift has a low profile to maintain stability on hard, compact surfaces like concrete. Scissor lifts can use an electric motor or a combustion engine to transport and lift the machine. Since the scissor lift functions on a vertical plane, if it needs to be repositioned horizontally, the operator will have to move it into place. The same lifting technology is used for the lifting components in regular scissor lift models as well as rough terrain models. Rough terrain scissor lifts are adapted for travelling on uneven locations. These machines rely on large allterrain tires to allow rough terrain scissor lifts to traverse difficult locations while offering higher ground clearance. Certain models offer 4WD making them able to traverse through dirty areas. The higher center of gravity works in conjunction with lower lifting heights. Scissor lifts can seem intimidating if you have not used one before. Images of swaying in the wind and being precariously balanced may come to mind. Feel secure knowing you will not feel the lift even moving and you will be in a stable position. Rigorous safety testing has to be completed prior to selling these machines. It is natural to feel unsure of these units until you can familiarize yourself with them. Safety precautions need to be maintained at all times. Understanding what you will be using your scissor lift for will help ensure you have the right type of model. The model you will prefer will largely depend on the types of jobs you plan on completing. How high you need to travel and how heavy the loads you will be transporting are all key factors. Extreme heights can be attained by different models depending on your specific application. Smaller models are commonly used for interior applications including warehouses and freight or factory settings. There is no need to purchase the largest model on the market if you are not going to require the fullest capacity. Optional railings and platforms are available on electrical scissor lifts to provide maximum safety. These units are safe and reliable. Many safety inspections and specifications need to be maintained in order for these industrial machines to be available for sale. These machines help us facilitate tasks that would otherwise not be possible. These lifts elevate vertically; therefore, the machine is parked in place prior to lifting. The operator needs to move the unit into the correct position before engaging the lift. There are a variety of safety features incorporated into the design. Following operational guidelines is essential for everyone's safety. The scissor lift's safety basket creates a secure work area compared to trying to accomplish similar tasks from a ladder or scaffolding. The majority of scissor lifts utilize batteries that are internally mounted inside of the base of the lift to generate power. Charging is required after a long sitting for an extended time or working a long shift. Many operations charge their equipment daily or change batteries every twelve hours. To charge the scissor lift, the operator parks it close to an electrical outlet within a well-ventilated location. The emergency shut-off switch is engaged upon parking to prevent other operators from driving off while plugged in. The sizeable red button found inside of the basket or the lift located near the charger or control box is the emergency shut-off switch. The battery charger is commonly located on the right side of the lift on the base. Many older models may feature the battery charger mounted on the back of the scissor lift. The charger for the machine is plugged into the AC extension cord within a well-ventilated area and the extension cord plugs into an electrical outlet. The length of the electrical cord on the battery charger needs to be short to prevent damage or running over it. There is a high possibility of danger if the extension cord dropped out of the battery charger while the machine is in operation. After the scissor lift plugs in to charge, all of the lights should become lit up. The batteries will automatically begin charging once plugged in. After the charging is complete, the battery lights switch to green and the charger shuts down. Older scissor lifts need to use a meter to show zero volts once they are completely charged and this charger also turns off after completion. After the scissor lift is

completely charged, the unit is ready to get back to work. Many places employ their scissor lift day by having additional batteries continually charging.	for 24 hours